



WV-ASM10

(System Controller WV-CU950 and monitor displays are optional.)

## i-Pro management and monitoring software for multi-recorder multi-site system

### Key Features: WV-ASM100/WV-ASM100L

- Up to 100 recorders, 64 encoders and 256 directly connected cameras can be registered. Up to 6,400 cameras registered in the recorders and 256 cameras registered in the encoders are automatically registered in the WV-ASM100 (the number of the cameras depends on the recorder and encoder).
- Live images can be received directly from the camera/encoder or via the recorder enabling flexible network design.
- Multi-Monitor option enables simultaneous use of operation display (1 / 4 / 9 / 16 split), Live display (1 / 4 / 9 / 16 split) and Map display each on a dedicated monitor. Single or two monitor operation is also available. A total of 20 screens can be displayed with the simultaneous use of the operation display and the live display at a time.\*1
- Up to 30 ips/camera can be displayed in 16 split-screen in MPEG-4 2 Mbps mode (depending on the camera and camera setup).
- Up to 400 camera groups: Cameras and multiscreen mode for the operation display can be programmed and called up by manual or sequence operation.
- Image resolution dynamically changes depending on the screen mode: VGA for Quad screen, QVGA for 16 split screen, enabling optimum network usage (depending on the camera model).
- Panasonic camera control: Pan/Tilt, Zoom, Focus, Brightness, Preset position call and program (up to 256), Auto mode, AUX 1 ~ 3, Click Centering, Wheel Zoom (depending on the camera model)
- A camera, a group or a sequence can be called up on the operation display by their ID with the optional system controller WV-CU950.\*1 The camera displayed in the active window can be controlled by the system controller. Recorder playback operation can also be made by the system controller with Jog/Shuttle.
- Alarm notification: A pop-up alarm message is displayed and live or playback images can be viewed by clicking the icon in the message.
- Illustrated camera, alarm and recorder icons for intuitive operations
- Up to 64 camera icons can be freely positioned on a map with alarm status indicated by the color of the icons.\*1
- Recorded images of up to 64 cameras (in the case of WJ-ND400) can be downloaded by one operation. Downloaded images can be viewed by the viewer software (provided).
- Sophisticated user management: User authentication with time limited password, 5 user levels, User-Camera View/Control partitioning in conjunction with recorder's user management function, Up to 32 user registrations
- System logs can be saved in CSV format. Operation logs can automatically be erased when specified time has passed (31 / 92 / 184 / 366 days).
- Audio from a camera can be heard and the operator voice can be transmitted to the camera's audio output through the network (single channel at a time, full/half duplex depending on the camera).

- Recorded audio with the WJ-ND200 or WJ-ND400 can be played back (single channel at a time).
- Motion frames with trails for the moving subjects can be displayed when used with the WJ-NT314.\*1
- When used with WJ-ND400, VMD search can be operated.

\*1 Not available for WV-ASM100L.

### Key Features: WV-ASM10


- WV-ASM10 i-Pro Monitoring Software provides up to 16 split live display including pre-programmed selection of cameras.
- Up to 16 recorders, 64 encoders and 256 directly connected cameras can be registered. Up to 512 cameras registered in the recorders and 256 cameras registered in the encoders are automatically registered in WV-ASM10 (the number of the cameras depends on the recorder and encoder).
- Spot / Quad / 6 split / 9 split / 16 split multiscreen and synchronized multiscreen group sequence
- Up to 30 ips/camera in 16 split-screen in MPEG-4 2 Mbps mode (depending on the camera)
- Up to 400 camera groups: User-programmable cameras and multiscreen assignment
- Pre-programmed cameras can automatically be displayed upon power ON.
- Camera title within 16 alphanumeric characters embedded in the image can be displayed.

### Optional Accessory

Ethernet System Controller  
with 3D-Joystick & Jog/Shuttle  
**WV-CU950**  
(For WV-ASM100 only)



### System Example



## Specifications: WV-ASM100/WV-ASM100L

<b>Supported Equipment</b>	Supported Cameras	Direct: Panasonic i-Pro series Network cameras except for WV-NM100 Via Recorder: Panasonic i-Pro series Network cameras, BB series (specific models) and Axis® (specific models)	
	Supported Recorders	WJ-ND400 series, WJ-ND300 series, WJ-ND200 series, WJ-HD309A/316A series, WJ-RT416 series	
	Supported Encoders	WJ-NT304, WJ-NT314	
	Supported Controllers*1	WV-CU950	
	Supported Image Format	MPEG-4 (i-Pro series except for WV-NM100), M-JPEG	
	Maximum Number of Recorder Registrations	100, Cameras registered in the recorders are automatically registered in WV-ASM100/WV-ASM100L	
	Maximum Number of Encoder Registrations	64, Cameras registered in the encoders are automatically registered in WV-ASM100/WV-ASM100L	
	Maximum Number of Camera Registrations	Camera direct: 256, Via Recorder: 6,400 (in the case of WJ-ND400), 3,200 (in the case of WJ-ND300A), Via Encoder: 256 (in the case of WJ-NT304, WJ-NT314)	
	<b>GUI Function</b>	Camera Control (depending on the Camera)	Pan/Tilt, Zoom, Focus, Brightness, Preset position call and program (up to 256), Auto mode (SEQ, SORT, AUTO PAN, PATROL, AUTO TRACK), AUX 1 ~ 3, Click centering, Wheel zoom
		Recorder Control (depending on the Recorder)	REC, PLAY, Rev PLAY, Pause, Stop, FF (up to 96x), REW (up to 96x), Prev Record, Next Record, Prev Image, Next Image, Skip (up to 60 min.), Rev Skip, (up to 60 min.) Text
Event Search		Target: Recorder (Camera) / Group / Map*1, Search criteria: Time date, Event type, Text	
VMD Search		In the case of WJ-ND400	
Multiscreen Mode		Spot / Quad (A-D) / 9 split / 16 split	
Sequence Display		10 programs, 64 steps/pattern, Spot / Quad / 9 split / 16 split Dwell time: 3s / 5s / 10s / 15s / 20s / 25s / 30s / 35s / 40s / 45s / 50s / 55s / 1min	
Display Performance		30 ips x 16 screens at MPEG-4 2 Mbps	
Multi-Monitor*1		Up to 3 monitors (Operation / Live / Map), Up to 20 cameras can be displayed (Operation-4, Live-16)	
Camera Group Display		Up to 400 groups with 16 alphanumeric titles	
Number of Maps*1		Up to 100 maps (JPEG or Bit map), Link: 64 cameras and 20 maps / map	
Image Download		Recorded images of up to 64 cameras (in the case of WJ-ND400) can be downloaded. Manual download only. Viewer software can be extracted from the main software.	
Camera Title Display		On the GUI, Up to 16 characters	
Clock Display		On the GUI, Time: 12H/24H, Date: 5 formats (When the image comes from the recorder)	
Alarm Source		Panasonic alarm protocol by Recorder	
Alarm Control		Reset, Auto reset (OFF / 10s / 20s / 30s / 1min / 5min)	
Alarm Action		Up to 16 alarm images can be displayed on the live monitor. Corresponding camera icon on the map lights up. Alarm message on the GUI and buzzer.	
Digital Zoom		Up to 4 times	
Text Attachment		Free comment can be attached for each record and reviewed at later time. Up to 200 characters	
System Log		Operation (100,000), System (1,000), Network error (1,000), Recorder error (1,000), Alarm (30,000)	
Recorder Log Download		Operator access, Network error, Error, Event	
User Management	Registration: Up to 32 users + Administrator, ID: 4-14 digit, PW: 4-8 digit, User level: 5 levels (Programmable), PW time limit: OFF / 31 / 92 / 184 / 366 days, Auto login: ON / OFF, Recorder login user: Up to 16 users		
Partitioning	User - Camera (View only, View & Control, No Access) in conjunction with recorder's user management		
Security Method	User authentication (ID and Password), Host authentication (IP address), Alteration detection, Hardware key (USB dongle)		
Time Synchronization	NTP (Server/Client)		
Summer Time	User definable (using menu setup)		
System Setup	Setup page in English, French, Italian, Spanish, German, Russian, Chinese		
GUI Language	English, French, Italian, Spanish, German, Russian, Chinese		
<b>General</b>	Supported OS	Microsoft® Windows® XP Home SP2, Microsoft® Windows® XP Professional SP2, Microsoft® Windows Vista® 32-bit, The language of the OS must be same as selected GUI language.	
	Required PC	CPU: Intel® Core™ 2 Duo 2.66 GHz or faster, RAM: 1 GB (for Microsoft® Windows® XP), 2 GB (for Microsoft® Windows Vista®) or more, VRAM: 128 MB or more, Microsoft® DirectX® 9.0c or later	
<b>Network</b>	Proxy	HTTP proxy supported (IP address and port No.)	
	FTP	Passive/Active	
<b>Viewer Software</b>	Playback Control	Play, Rev Play, Pause, FF, REW, Prev Record, Next Record, Prev Image, Next Image	
Additional Functions	Alteration detection, Save as JPEG, Two times zoom, Print		

\*1 Not available for WV-ASM100L.

## Specifications: WV-ASM10

<b>Supported Equipment</b>	Supported Cameras	Direct: Panasonic i-Pro series Network cameras except for WV-NM100 Via Recorder: Panasonic i-Pro series Network cameras, BB series (specific models) and Axis® (specific models)
	Supported Recorders	WJ-ND300 series, WJ-ND200 series, WJ-HD309A/316A series
	Supported Encoders	WJ-NT304
	Supported Image Format	MPEG-4 (i-Pro series except for WV-NM100), M-JPEG
	Maximum Number of Recorder Registrations	16, Cameras registered in the recorders are automatically registered in WV-ASM10
<b>Display Function</b>	Maximum Number of Encoder Registrations	64, Cameras registered in the encoders are automatically registered in WV-ASM10
	Maximum Number of Camera Registrations	Camera direct: 256, Via Recorder: 512 (in the case of WJ-ND300A), Via Encoder: 256 (in the case of WJ-NT304)
	Multiscreen Mode	Spot / Quad / 6 split / 9 split / 16 split
	Sequence Display	10 programs, 64 steps/pattern, Spot / Quad / 6 split / 9 split / 16 split, Dwell time: 3s / 5s / 10s / 15s / 20s
	Display Performance	30 ips x 16 screens at MPEG-4 2 Mbps
<b>General</b>	Camera Group Display	Up to 400 groups with 16 alphanumeric titles
	Camera Title Display	Up to 16 Characters (image embedded)
	Security Method	Hardware key (USB dongle)
	Time Synchronization	NTP (Server / Client)
	Summer Time	User definable (using menu setup)
	System Setup	Setup page in English, Chinese, Japanese
	Supported OS	Microsoft® Windows® XP Home SP2, Microsoft® Windows® XP Professional SP2, Microsoft® Windows Vista® 32-bit, The language of the OS must be same as selected GUI language.
<b>Network</b>	Required PC	CPU: Intel® Core™ 2 Duo 2.4 GHz or faster, RAM: 1 GB (for Microsoft® Windows® XP), 2 GB (for Microsoft® Windows Vista®) or more, VRAM: 128 MB or more, Microsoft® DirectX® 9.0c or later
	Proxy	HTTP proxy supported (IP address and port No.)

DISTRIBUTED BY:

## Major Operating Controls

**Operation Window**

Menu Bar      Tool Bar      Status Bar

Function Panel      Image Display Area      Operation Panel

**Tool Bar**

① [Save as JPEG file] Icon    ⑤ [Display images on the selected area] Icon  
 ② [Print] Icon    ⑥ [1] Icon    ⑨ [4C] Icon    ⑫ [16] Icon  
 ③ [Logout] Icon    ⑦ [4A] Icon    ⑩ [4D] Icon    ⑬ [Full screen] Icon  
 ④ [Display images on 1-screen] Icon    ⑧ [4B] Icon    ⑪ [9] Icon    ⑭ [Search] Icon

**Status Bar**

① Recorder Title / Camera Title    ⑤ [Audio reception] Button / ⑧ [COPY] / [DELETE]  
 ② [ALM] Button    [Audio transmission] Button    ⑨ Time & Date  
 ③ [ERR] Button    ⑥ [LIVE] / [PLAY] / [SD PLAY]  
 ④ [SD] Button    ⑦ [REC] Indicator

**Playback Operation Panel**

① [REW] Button    ⑨ [PAUSE] Button  
 ② [PREV RECORD] Button    ⑩ [STOP] Button  
 ③ [REV PLAY] Button    ⑪ [NEXT IMAGE] Button  
 ④ [PLAY] Button    ⑫ [SKIP] Button  
 ⑤ [NEXT RECORD] Button    ⑬ SKIP TIME  
 ⑥ [FF] Button    ⑭ [Speed] Button  
 ⑦ [REV SKIP] Button    ⑮ [TEXT] Button  
 ⑧ [PREV IMAGE] Button    ⑯ [REC START] / [REC STOP] Button

**Camera Operation Panel**

① Zoom    ③ Auto Mode    ⑤ Brightness    ⑦ AUX  
 ② Focus    ④ Control Pad    ⑥ Preset

### Trademarks and registered trademarks

— Microsoft, and Windows are registered trademarks of Microsoft Corporation in the U.S. and other countries.

— Axis is a registered trademark of Axis Communications AB.

— Intel and Pentium are registered trademarks of Intel Corporation.

### Important

— Safety Precaution: carefully read the operating instructions and installation manual before using this product.

— Panasonic can not be responsible for network performance and/or other manufacturer products that reside on the network.

- All TV pictures/menu are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.
- Product pictures shown in this catalog are all NTSC models.

**Panasonic**®

<http://panasonic.net/security/>

Printed in Japan (2A-006DL)